



MAKER SUPER TAURO SYNTH

Description

High performance lubricant fluids. Formulated with specially selected synthetic bases (PAO, esters) and latest generation additives, specially suitable for applications under very severe working conditions: high loads, low speeds and high/low temperatures. They are specially suitable for industrial bearings and gears subject to very severe working conditions (high loads and low speeds) and within a wide range of temperatures. These include systems based on the forced circulation of oil, oil bath or splash lubrication. They are specially suitable for working at high temperatures, as their excellent resistance to oxidation allows extension of time between replacements, saving oil change, equipment cleaning and shutdown costs.

Properties

Exceptional resistance to oxidation at high temperatures.
Very low pour point, allowing operation at low temperatures.
Very high viscosity index, allowing lubrication within a wide range of temperatures.
Lower friction coefficient than conventional oils, thereby reducing power consumption.
Compatible with conventional elastomers, joints and paints.
Miscible with mineral oils.
Excellent water separation and anti foam properties.
Very good anti rust and anti corrosion protection.
Optimum EP properties.

Quality levels, approvals and recommendations

- AGMA 9005-F16 (antigua 9005-E02-EP)
 - AIST 224 (US Steel 224)
 - DANIELI STANDARD N. 0.000.001 - REV.15 (150, 220, 320, 460)*
 - DIN 51517/3 - CLP
 - FIVES CINCINNATI P-35 (460)
 - FIVES CINCINNATI P-59 (320)
 - FIVES CINCINNATI P-74 (220)
 - FIVES CINCINNATI P-76 (100)
 - FIVES CINCINNATI P-77 (150)
 - FLENDER Aprobado por FLENDER Gear Units Rev.16 (150, 220, 320, 460)*
 - ISO 6743/6 CKT
 - REINTJES BV1597/2, BV1917/2 (100)*
 - REINTJES BV1597/4, BV1917/4 (150)*
 - THYSSENKRUPP 41,42,43 y 44 (Engranajes CLP PAO) (150, 220, 320, 460)*
 - ZANINI RENK 00-90263/4n*
- *Formal approval



MAKER SUPER TAURO SYNTH

Technical specifications

	UNIT	METHOD	VALUE				
ISO Viscosity Grade			100	150	220	320	460
Kinematic viscosity at 40 °C	cSt	ASTM D445	100	150	220	320	460
Kinematic viscosity at 100 °C	cSt	ASTM D445	14.5	19.4	25,7	34,9	47.2
Viscosity index	-	ASTM D2270	148	148	148	154	161
Flash point, open cup	°C	ASTM D92	205	272	250	256	252
FZG (A/8,3/90): Failure load stage	-	ISO 14635	>12	>12	>12	>12	>12
Pour point	°C	ASTM D97	-54	-51	-42	-42	-39
Rust, method A	-	ASTM D665	Pass	Pass	Pass	Pass	Pass
Timkem load	lb	ASTM D2782	70	70	70	70	70
Water separability, Free water	cm3	ASTM D2711	<37	<37	<37	<37	<37

The above mentioned characteristics are typical values and should not be considered product specifications.