



RIDER TOWN 4T 20W-50

Description

Refined lubricant oil especially designed for 4-stroke petrol engine motorcycles the greater part of whose activity is developed in an urban environment. Its additives prolong its life in this type of working conditions.

Properties

- Guarantees good lubrication in normal service conditions
- Prevents the formation of lacquers and varnishes thanks to its dispersant additives.
- Its degree of viscosity guarantees perfect performance in warm atmospheres.
- Its detergency ensures the piston is properly cleaned.
- It maintains an adequate pressure and temperature under all service conditions.

Quality levels, approvals and recommendations

• API SJ

• JASO T 903:2023 MA2*

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			20W-50
Density at 15 °C	g/cm3	ASTM D4052	0.885
Kinematic viscosity at 40 °C	cSt	ASTM D445	166
Kinematic viscosity at 100 °C	cSt	ASTM D445	19
Viscosity index	-	ASTM D2270	132
CCS Viscosity at -15 °C	cP	ASTM D5293	>9,500
HTHS, viscosity at 150 °C	cP	ASTM D5481	>3.7
Flash point, open cup	°C	ASTM D92	248
Noack volatility, 1h at 250 °C	% in weight	CEC L-40-93	6.2
Pour point	°C	ASTM D97	-24
Shearing Inj.Bosch: Vis 100 °C (30 cy)	cSt	CEC L-14-93	>16.3
TBN	mg KOH/g	ASTM D2896	7

The above mentioned characteristics are typical values and should not be considered product specifications.

Safety data sheets are available at: <https://lubricants.repsol.com/en/>

Lubricant Technical File RP_2131T

February 2025