



GUARD BRAKE FLUID DOT 4 XT1

Description

Special product based on polyethylene glycols for use in severe operating conditions and high performance. Recommended for vehicles and all braking systems that require a product with this quality level. It should not be mixed with brake fluids of another level of quality, or added to products that have already been used. Instead, the liquid in the braking system must be completely changed.

Properties

- High boiling point: above 240 °C.
- Avoids the formation of foam
- High stability against the presence of moisture in the circuit thanks to its high wet boiling point
- Great thermal stability.
- Compatible with joints and gaskets, thus avoiding product loss risks.
- Contains inhibitors that prevent corrosion of the metal circuit components.
- Corrosive to the bodywork.
- Store in the original container and in a dry place.

Quality levels, approvals and recommendations

- FMVSS: 116 - DOT 3 y DOT 4
- ISO: 4925 Class (3, 4)
- SAE: J 1703/J 1704

Technical specifications

	UNIT	METHOD	VALUE
Appearance	-	Visual	Clear and bright
Water content	%	FMVSS 116	0.14
Density at 20 °C	g/cm ³	ASTM D891	1.063
Viscosity at -40 °C	cSt	FMVSS 116	<1500
Reflux boiling point	°C	FMVSS 116	>240
Wet boiling point	°C	FMVSS 116	>155
pH value	-	FMVSS 116	>7,0

The above mentioned characteristics are typical values and should not be considered product specifications.