



# MAKER DESMOLDOIL

## Description

Products from the DESMOLDOIL range are compounds formulated to act as mould-release agents in various applications and as process oil also. They contain a selected mix of oils, which include appropriate additives, and have been treated to fulfil their function.

The range of DESMOLDOIL products has been carefully analysed to guarantee compliance with our customers demands in relation to all kinds of applications and finishes (pieces of concrete, formwork, etc.) on any kind of surface, such as wood, iron, etc.

## Properties

- Good oxidation resistance and storage stability.
- Excellent mould release properties.
- Environmentally friendly (can not be labelled).
- Exceptional coverage.
- Excellent finish.

## Technical specifications

	UNIT	METHOD	VALUE		
			90	L	P
Colour	-	ASTM D1500	<1	0.5	0.5
Density at 15 °C	g/cm3	ASTM D4052	0.857	0.868	0.873
Kinematic viscosity at 40 °C	cSt	ASTM D445	11.5	24.0	28,6
Kinematic viscosity at 100 °C	cSt	ASTM D445	3.3	4,3	4.9
Pour point	°C	ASTM D97	-9	-12	-14
Flash point, open cup	°C	ASTM D92	>160	>170	>190
Additives			No	No	Yes

The above mentioned characteristics are typical values and should not be considered product specifications.