



MAKER DESMOLDOIL R

Description

Products from the DESMOLDOIL range are compounds formulated to act as mould-release agents in various applications and as process oil. They are made up of a selected blend of bases. More specifically, part of the MAKER DESMOLDOIL R base is regenerated, contributing to the recycling of these products as well as fulfilling the technical requirements for the mould release of concrete elements.

The DESMOLDOIL product range has been carefully assessed to ensure compliance with our clients requirements, in any kind of application and finish (concrete parts, shuttering, etc.) or for any kind of mould with wooden, iron soft-metal, or other surfaces.

Properties

- Good oxidation resistance and storage stability.
- Excellent mould release properties.
- Environmentally friendly (can not be labelled).
- Exceptional coverage.
- Excellent finish.

Technical specifications

	UNIT	METHOD	VALUE
Colour		ASTM D1500	1.5
Density at 15 °C	g/cm ³	ASTM D4052	0.853
Viscosity at 40 °C	cSt	ASTM D445	24
Viscosity at 100 °C	cSt	ASTM D445	4.7
Viscosity index	-	ASTM D2270	100
Flash point, open cup	°C	ASTM D92	220
Pour point	°C	ASTM D97	-18

The above mentioned characteristics are typical values and should not be considered product specifications.