



# MAKER HYDROFLUX EP

## Description

The lubricants included in this range are manufactured using selected and carefully additivated bases to make them hydraulic oils for general use.

These oils are specially suitable for most hydraulic circuits, including those requiring special anti-wear protection, both in industry and motoring (dumpers, civil works machines, etc.), regardless of the type of pump with which they are equipped and pressures under which they work.

## Properties

- Resistance to oxidation, ageing and sludge formation.
- Low pour point.
- High viscosity index.
- Compatible with joints.
- Good anti-foam properties.
- Marked anti-wear properties.
- Easy water separation.

## Quality levels, approvals and recommendations

- GIA: Extrusion Systems\* (46, 68)
- AFNOR: NF ISO 11158 HM, 48-690, 48-691 (100, 32, 46, 68)
- DIN: 51524-HLP (100, 32, 46, 68)
- ISO: 6743/4 HM, 11158 (100, 32, 46, 68)

\*Formal approval

## Technical specifications

	UNIT	METHOD	VALUE				
ISO Viscosity Grade			22	32	46	68	100
Viscosity at 100 °C	cSt	ASTM D445	4.3	5.4	6.7	8.6	11.1
Viscosity at 40 °C	cSt	ASTM D445	22	32	46	68	100
Viscosity index	-	ASTM D2270	103	104	97	97	97
Density at 15 °C	g/cm3	ASTM D4052	0.865	0.863	0.872	0.880	0.888
Flash point	°C	ASTM D92	210	226	231	246	264
Pour point	°C	ASTM D97	-24	-24	-24	-24	-21
FZG, damage stage	-	DIN 51354	-	11	11	11	11
Four ball wear, scar diameter (1h, 40 kg, 75 °C)	mm	ASTM D4172	0.50	0.50	0.45	0.45	0.45
Res. to oxidation, NN after 1 500 hrs	mgKO H/g	ASTM D943	<2	<2	<2	<2	<2
Water separability ((1) 54°C/(2) 82°C)	mín	ASTM D1401	<20(1)	<20(1)	<20(1)	<30(1)	<30(2)



# MAKER HYDROFLUX EP

## Technical specifications

	UNIT	METHOD	VALUE				
Corrosion Cu, 3hrs 100 °C	-	ASTM D130	1b	1b	1b	1b	1b
TAN	mg KOH/g	ASTM D664	0.38	0.38	0.38	0.38	0.38
RPVOT	min	ASTM D2272	400	400	400	400	400

The above mentioned characteristics are typical values and should not be considered product specifications.