



MAKER SUPER TAURO

Description

The Maker Super Tauro range of oils has been developed for applications in industrial gear assemblies with high load requirements. Its careful formulation incorporates the highest quality bases and additives, improving its anti-rust properties, its anti-foaming capacity and its resistance to oxidation. As such, these oils offer an excellent performance that puts them ahead of their competition.

They are particularly suitable for all kinds of industrial reducers and multipliers, using splash or circulating lubrication.

Very effective in all cases requiring maximum levels of oxidation resistance and/or load capacity.

Properties

- Reduce wear under boundary lubrication conditions and extreme pressure
- Excellent thermal stability
- Very good protection against rust, preventing steel corrosion
- High de-emulsifying capacity (quick separation from water)
- Good antifoaming characteristics
- Resistance to the rupture of the lubricant film

Quality levels, approvals and recommendations

- DANIELI: STANDARD N. 0.000.001 - REV.15* (150, 220, 320, 460, 680)
- IBERCISA* (220, 320)
- MANULI: Gear* (320)
- REINTJES: BV1597/2, BV2060/2* (100)
- SCHOTTEL: GOST 23652-79 TAP-15V * (100, 150, 220, 68)
- AGMA: 9005-F16 (100, 1000, 150, 220, 320, 460, 68, 680)
- BATTENFELD (68)
- DIN: 51517/3 - CLP (100, 1000, 150, 220, 320, 460, 68, 680)
- Fives Cincinnati: P-35 (460)
- Fives Cincinnati: P-69 (320)
- Fives Cincinnati: P-76 (100)
- Fives Cincinnati: P-78 (1000)
- ENGEL: Engel Injection Moulding Machines* (320)
- LEMASA* (220)
- NEGRI BOSSI: ELEOS, eCANBIO JANUS Y VESTA series* (320, 68)
- REINTJES: BV1597/4, BV2060/4 * (150)
- SIEMENS: Gamesa GearBox* (100, 1000, 150, 220, 320, 460, 68, 680)
- AIST: 224 (US Steel 224) (100, 1000, 150, 220, 320, 460, 68, 680)
- DAVID BROWN: S1.53.101 Type M, A & E (100, 1000, 150, 220, 320, 460, 68, 680)
- Fives Cincinnati: P-34 (680)
- Fives Cincinnati: P-63 (68)
- Fives Cincinnati: P-74 (220)
- Fives Cincinnati: P-77 (150)
- ISO: 12925-1 CKD (100, 1000, 150, 220, 320, 460, 68, 680)

*Formal approval



MAKER SUPER TAURO

Technical specifications

The above mentioned characteristics are typical values and should not be considered product specifications.