

QUALIFIER TRANSMISSION 10W-40

MOTO

Description

Lubricant oil formulated for lubricating motorcycle gearboxes. It provides excellent resistance to shearing and ensures that oil bath clutches operate with perfect slipping control in extreme conditions. It prolongs the life of all gearbox components, reduces mechanical noise and helps cold starts..

Properties

- Maximum protection against wear and extreme conditions for all parts of the gearbox.
- Provides optimum friction in clutch discs, preventing slippage.
- Enables speed and clutch changes to be carried out smoothly and precisely.

Quality levels, approvals and recommendations

- API SL
 - JASO T-903:2016 MA2*
- *Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm ³	ASTM D 4052	0,854
Viscosity at 100 °C	cSt	ASTM D 445	14,1
Viscosity at 40 °C	cSt	ASTM D 445	89
Viscosity at -25 °C	cP	ASTM D 5293	7000 maximum
Viscosity index	-	ASTM D 2270	160
Flash point, open cup	°C	ASTM D 92	244
Pour point	°C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	7
Sulphated ashes	% weight	ASTM D 874	0,8

The above mentioned characteristics are typical values and should not be considered product specifications.