



RACING SNOW 4T 0W-40

Description

Synthetic lubricant oil for snow motorcycles driven by 4-stroke engines and developed to meet the demands of the main manufacturers. It displays excellent behaviour at low temperatures thanks to its low viscosity; it enables the engine to develop maximum performance in intense cold or when there is snow, and it achieves perfect lubrication of the different engine elements in extreme environmental conditions.

Properties

- Low pour point, allowing its use under temperatures below zero.
- Its carefully researched viscosity provides a smooth flow at low temperatures, maintaining the lubricating film and the level of protection required for engines at these temperatures.
- Its modern formula endows this oil with magnificent antiwear, dispersant and antioxidant properties, improving the engine's performance.

Quality levels, approvals and recommendations

• T 903:2023 MA*

• API: SN

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			0W-40
Density at 15 °C	g/cm ³	ASTM D4052	0.845
Kinematic viscosity at 100 °C	cSt	ASTM D445	13.4
Kinematic viscosity at 40 °C	cSt	ASTM D445	76
CCS Viscosity at -35 °C	cP	ASTM D5293	6047
Flash point, open cup	°C	ASTM D92	225
Pour point	°C	ASTM D97	-57
TBN	mg KOH/g	ASTM D2896	7.1
Sulphated ashes	% in weight	ASTM D874	0.8
Shearing Inj.Bosch: Vis 100 °C (250 cy)	cSt	CEC L-14-93	11.65

The above mentioned characteristics are typical values and should not be considered product specifications.